



Ensemble based machine learning algorithms in 6g for VANET

A.Velayudham,

Professor and Head,

Department of Computer Science and Engineering,
Jansons Institute of Technology, Karumathampatti,
Coimbatore-641659 , sunilvel@gmail.com

K.Madhan Kumar

Professor/ECE

PET Engineering collegeVallioor 627117

madhankn@gmail.com

M.Pavithra,

Assistant Professor,

Department of Computer Science and Engineering,
Jansons Institute of Technology, Karumathampatti,
Coimbatore-641659 nks110730@gmail.com

M.S Krishna Priya,

Assistant Professor,

Department of Artificial Intelligence and Data Science,
Jansons Institute of Technology,
Karumathampatti, Coimbatore-641659
krishnamspriya@gmail.com

878

Abstract

The vehicular adhoc network (VANET), a developing study area in the intelligent transportation system, provides the network's vehicles with crucial information. Road accidents harm around 160 000 people;thus, they must be reduced, and VANET safety must be improved. The ability to foresee traffic jams is crucial for reducing vehicle accidents and enhancing pedestrian traffic flow. However, deep learning models' performance in foretelling traffic congestion on roadways is hampered by the network's dynamic behaviour of the vehicles.The utilization of AI in 6G vehicular organizations to help vehicular application administrations is a hotly debated issue for the latest examination works in the writing and is at present the subject of broad review. This paper offers a careful investigation of past examinations that consolidated support and profound support learning calculations for the administration of vehicular organizations, with an emphasis on vehicular broadcast communications troubles. Then, we go through RL and, in particular, DRL techniques to deal with new problems in 6G vehicular networks. Finally, we talk about and point out certain issues that need more research.

Keywords: Vehicular Ad-hoc network (VANET), Deep learning, Intrusion Detection,6 G Technology



Introduction

A VANET is a versatile organization that permits vehicles to speak with one another without even a trace of fixed foundation, determined to increment street wellbeing through the trading of cautions between vehicles. VANETs are another kind of Mobile Adhoc Networks (MANETs). VANET is comprised of On-Board Units (OBUs) and Road Side Units (RSUs) (RSUs). VANETs are basic to the advancement and utilization of self-driving and semi-self-driving vehicles. Interior and outer correspondence frameworks are significant parts in self-driving and semi-independent vehicles. One of the most important goals of VANET is safety. Because safety reduces accidents, saves lives, and reduces traffic. Other services, such as Internet access, weather forecast, and geolocation information, can enhance the travel experience by providing comfort, convenience, and information.

Lately, there has been an expansion in the quantity of people killed in car crashes, which must be addressed in order to preserve lives. The main causes of road accidents include user behaviour, infrastructure, environmental conditions, and technical errors in roadways [17, 18]. One of the issues that must be addressed in the transportation system is traffic congestion [19]. As population growth has quickened, so has the quantity of automobiles over the road, resulting in traffic congestion, accidents, and pollution [20]. Because VANET vehicles travel at such high speeds, topology changes are frequently dynamic, posing a number of difficulties for routing research⁵. For instance, in a VANET, vehicular traffic is often restricted to bidirectional movements on roads and highways. The roads and streets in VANET, which have a tendency to be predictable⁶, serve as a constraint to the activity of autos. Each vehicle can then keep track of both its present position and its past travels. By doing

this, vehicles may predict how they and their neighbours will move in the future.

Moreover, it is expected that the correspondences accomplice's positional directions are now known in place-based steering. Position-based steering is consequently viewed as one of the most mind-blowing VANET innovations. There is a great deal of writing on broadcast techniques for impromptu networks⁸. They centre their endeavours around few arrangements that better match the models of VANETs⁹ because of the restricted measure of room accessible. Flooding is an easy way to create a broadcast service, in which every car broadcast messages to all of its neighbours in addition to the one it received from. Flooding achieves good performance for a limited number of nodes by ensuring that the message eventually reaches every node in the network¹⁰. Additionally, it is simple to use. Performance, however, drastically degrades as the network's nodes multiply. Position-based Schemes expect hubs to know about that situation to have a higher capacity to bear hub development.

Collisions in traffic are caused by inadequate traffic management, [17, 21] poor law enforcement, poor infrastructure, and signal failure. The prevention of future transportation fatalities is a visible aftereffect of traffic of vehicles on highways, [22] cities, and city area. Ammunition on the road includes monitoring of traffic and channelling, as well as various technology riveting alarm systems and digital maps. [23] Vehicle active safety plays an important role in collisions system of warnings.

Congestion could be reduced by recognising traffic jams, estimating congestion levels, providing information about current traffic conditions, and offering different routes [24, 25]. As a result, in order to alleviate traffic congestion, the system must predict traffic



jams. Forecasting the incidence of crashes based on the number[26, 27]. of crashes recorded for a specific time period at a specific place is beneficial in highway monitoring. Avoiding auguring collisions will have a significant impact on minimising road concussion [28]. The demurrer in the vehicular networks takes into account the cars' rapid movement as well as communication disassociation and conjunctions [29-34].

The transportation issue is a significant organization organized direct programming (LP) issue that surfaces generally speaking and has stood out enough to be noticed in the writing, as it ought to. The principal thought of this issue is to find the base complete expense of shipping a decent from its starting points to its objections with the goal that the stockpile at the beginnings can satisfy the need at the objections. The transportation problem can be used in many different ways, including scheduling, production, investment, deciding where to put a plant, and keeping track of inventory. Usually, transportation problems are solved by assuming that the supply and demand, as well as the costs of transportation, are clear. But in many cases, the person making the decision doesn't know the exact coefficients for the transportation problem. Fuzzy sets can be used to define the problem's coefficients or elements when the information isn't clear or precise. This makes fuzzy transportation problems possible (FTPs).

Review of Literature

The hybrid AI based model was utilized to mirror and dissect the undertaking of an uncommon car traffic stream figure framework, as indicated by Boukerche et al.17's 2020 distribution. They focus on upgrading the elements of the expectation model that is utilized to set the model in motion. They give a pristine cross breed profound learning model which is based on

the profound total construction of the Gated Recurrent Unit (GRU) and the Graph Convolutional Network (GCN). For the web-based expectation challenge, the web-based forecast strategy depends on refinement learning. An effective parallel training method is used to improve the model's precision and effectiveness while utilising the structure of the vehicular cloud.

The mental radio vehicular organization was presented in 2021 by Hossain et al.18 using AI based supportive reach recognizing in strong division. Roads are isolated into comparable pieces and a while later distributed perspective on the probability regard. By combining cushioned and Nave Bayes estimations, express vehicles or various clients can give area identifying data that are used by a cross variety AI computation to pick the ideal reach distinguishing (SS) approach. The pleasant SS overall decision was made by the piece range subject matter expert (SSA) using the tri-expert help learning (TA-RL) method.

Automatic vehicles have become increasingly popular in recent years. To communicate information, all of the vehicles are linked together via the internet. When an attacker attempts to hack the information between two cars, and the message arrives at its destination after a particular delay, there is a risk of an accident. Many algorithms have been created, including: In this paper, KNN (K Nearest Neighbor) and SVM (Support Vector Machine) AI strategies were utilized to recognize different types of assaults in a vehicular impromptu organization. KNN and SVM are both utilized for information characterization and relapse. DoS and fluffy assaults can be recognized in this exploration. It introduced a multi-facet perceptron (MLP) brain organization to recognize gatecrashers or assailants on an IoV (Internet of Vehicles) network in A multi-facet Perceptron-Based



Distributed Intrusion Detection System for Internet of Vehicles [2].

Uzma Khan et al. distributed an examination on Detection of Malicious Nodes (DMN) in Vehicular AdHoc Networks in 2014. A half and half spine based grouping strategy is proposed in this review. To choose the group head, the proposed calculation utilizes a spine known as bunch initiative. More characteristics, such as a vehicle's distance, density, and geographical position, may be addressed in the future.

The Intrusion Detection System [3] proposed using a peculiarity based location way to deal with recognize deceitful data revealing by maverick hubs in the organization. To assess the framework, the Road Side Unit (RSU) was sent inside the correspondence ranges, covering the full test geographic locale. Each hub computing the worldwide boundary stream will get meta-information from RSUs inside the hub's correspondence range. Subsequently, the vehicle's area can be kept mysterious. Maverick hubs are brought into the framework, and interruption recognition frameworks (IDS) are utilized to identify them. Intrusion detection utilising deep belief network and probabilistic neural network [4] In this paper, an intrusion detection system is created just for the network, and deep belief network is used for attack classification.

Utilizing large information examination, Hebert et al. foster a high-goal mishap expectation model for foreseeing the conditions of a mishap inside the space of hours on sections of street assigned by crossing points. Huge information investigation is an arranged system that permits information researchers to separate significant data from gigantic measures of heterogeneous and complex information. The reasonable arbitrary woodland method is utilized to address or test information irregular characteristics, and various AI calculations, for example, choice trees, counterfeit brain organizations, and Bayesian organizations help in determining the

probability of street mishaps. The conditions of street mishaps can be effectively anticipated by using factors and boundaries in the dataset, for example, weather conditions ascribes, blood vessel section credits, and date and time credits. To further develop execution, a few data like the area and timing of street development action, as well as populace thickness, should be added to the dataset.

Bang and Lee [25] anticipate the normal situation in stirrings and bearing of every transport to stay away from mixture or access of impact in-between the vehicles. The vector-based versatility figure model in the TDMA-based VANET dodges impacts by designating time allotments and conjectures the portability of neighbouring vehicles by using the residence data of the control schedule opening, vehicle's ID, course of the vehicle mix, bounce data, and a vehicle's scope and longitude. The algorithm's performance is improved in road environments with high traffic density and conveyances that are continually agitating and recasting route directions. Access and amalgamate crashes occur as a result of vehicle movement patterns and traffic conditions.

Deep Neural Network Algorithm

Deep belief networks are type of of deep brain network calculation which is based after the human mind, permitting them to really detect portrayal and communication complex data more. Deep Belief Networks are a graphical portrayal that is essentially generative in nature, delivering all likely qualities for the situation within reach. It consolidates likelihood and measurements, as well as AI and brain organizations. Profound Belief Networks are included different layers containing values, with an association between the layers anyway not the characteristics. The fundamental goal is to help the structure in orchestrating the data.

Methodology



Seagull Optimization algorithm

The Seagull Optimization Algorithm (SOA) contains two pivotal methodology that assistance in the effective choice of the group chief: movement and going after. The Migration stage first mirrors gulls flying starting with one area then onto the next. Impact aversion, moving toward ideal neighbours, and staying near the best hunt specialist are the three fundamental requests of the seagull.

Collision prevention

The collision between neighbour search agents is diminished in this stage using additional variable A^* . The " A^* " is used to locate the position of the next search agent, which is symbolised through,

$$P_s^* = A^* \times P_s^*(X).$$

Where, P_s shows a search agent's position to prevent clashing with other search agents, $P_s(x)$ shows the search agent's current location or position, while A shows the movement of search agents inside a certain search space.

$$A^* = f_A - (X' \times \left(\frac{f_A}{MAX_{iter}^*} \right))$$

The term " f_A " is used to adjust the frequency of the variable " A^* ," where f_A is initially set to 2 and thereafter gradually reduced to "zero." When a collision is avoided, the search agent indicates the best area.

$$P_{SA} = B^* \times (P_{bs}^*(x) - P_s^*(X)).$$

However, P_{SA} offers the top most search agent positioned P_s^* with the site of Search agent P_s . In this scenario, the variable " B^* " is utilised at the random to control the ratio of exploration to exploitation. The mathematical formulation of B^* is shown in the following equation.

$$B^* = 2 \times A^{2*} \times RD.$$

Although RD represents the random value $[0, 1]$, the following equation updates the search agent's position based on the best search agent.

Approaching the best position

$$D_s^* = |P_s^* + P_{SA}|.$$

D^*S , however, stands for the separation between the search agent and the ideal search agent.

This approach was developed after reviewing earlier search techniques. In the air, prey is attacked using the spiralling technique. In this procedure, the three planes X' , Y' , and Z' are significant. Each plane is described in the paragraphs that follow.

$$X' = R' \times \cos K',$$

$$Y' = R' \times \sin K',$$

$$Z' = R' \times K',$$

$$R' = U' \times e^{K'V'}$$

where R' denotes that each turn radius takes the relevant component into account. The spiral in the search space is created by several turns between U' and V' . These consonants describe the spiral form. K' stands for a

$$[0 \leq K' \leq 2\pi].$$

random number with the range

The base of the real logarithm is e .

Based on better unidentified conduct, the position of the vehicle

Fish moving randomly in their area of vision is an example of random behaviour. The fish will pick a state at the random from its visual sector if its ongoing state, i is P_s^* (current state as determined via Seagull optimization).

The moving procedure is as follows:

$$P_{s/next}^* = P_s^* + visual + Rand().$$

Here, the fish's visual field is indicated by Visual, and a random number between 0 and 1 is indicated by $Rand()$. With AFSSO-VANET, the present vehicle position P_s^* , as determined by Seagull Optimization, will be improved.

following behaviour

The imitation fish that have the most fulfilment of food in their visual sector migrate closer to them as a result of their actions.



$$P_{s/next}^* = P_s^* + \frac{B^*(P_s^* - X_j)}{B^*[[X_j - P_s^*]]} \times step \times Rand ()$$

According to the nature of the seagull optimization method, the following behaviour is added to the variable B in above Eq to enhance its performance. When all of the algorithm's iterations have been completed, the algorithm is considered to have reached its optimal state, which is the state depicted on the noticeboard. In this case, the Cluster Head choice based on Fitness value is quite important. After that, the procedure is repeated for the neighbouring node to make sure that every node is given the highest

fitness score. On the other side, a collective learning strategy is used to lessen the impact of a blackhole attack in network locations. An ensemble learning strategy based on the ANN, SVM, DT, and Navie Bayes algorithms is used to calculate the performance because this type of assault reduces the network efficiency. The HFSA-VANET outcomes obtained in this model are assessed using all ensemble learning strategies. By recognising and categorising the attacks, each will produce a different set of findings, which will aid in deciding the optimum outcomes. The suggested model's flowchart demonstrates how the ensemble technique helped the model get better outcomes with HFSA-VANET.

883




Figure 1: Model Architecture

Results & Discussion

Results and analysis of the techniques for enhancing machine learning with the hybrid optimization method to forecast mobility in VANET that were suggested and put into practise. The project's (HFSA-VANET) execution is assessed and contrasted with the existing approach (CRSM-VANET). To compare proposed (HFSA-VANET) and existing (CRSM-VANET)29 approaches, delay, energy


utilization, drop, throughput, and reasonableness record quantifiable qualities are registered and thought about

Below, the HFSA-VANET and the CRSM-delay, VANET's energy usage, drop, throughput, and fairness ratio are to be compared.


The suggested method achieves the following results in node 20: 98 J, 0.093680, 0.897709 for energy taken, value of delay, and value of

drop. Additionally, the throughput of the new method, which is higher than the old one, is 31,342. The present method has a value of 9.000000, whereas the proposed method has a fairness score of 8.000000. The suggested solution achieves 47 J, 9.752926, and 0.472095 for energytaken , value of delay, andvalue of drop in node 70. Additionally, compared to the old approach, the new one achieves a Throughput of 31,342. In


comparison to the current method, the proposed strategy has a fairness score of 4.000000 as opposed to 3.000000. In node 60, the suggested method obtains the following results for energytaken , value of delay, andvalue of drop: 36 J, 10.902826, and 0.376634. The proposed method also achieved a Throughput of 28,424 as opposed to the present procedure's 26,749 Throughput.



Graph 1: Plot of delay in existing and proposed model



Graph 2: Plot of consumption of energy in proposed and existing method



Graph 3: Drop plotting of proposed and pre-existing model

1890 J, 380.116000, 18.883763 for energy utilization, defer worth, and drop esteem in speed 40 are the consequences of the proposed strategy. Moreover, the new technique outperforms the ongoing system with a Throughput of 35. The current strategy has a score of 5.000000 while the proposed way has a decency worth of 4.000000. The proposed strategy accomplishes 2230 J, 655.169558, 22.597975 as far as energy use, deferral, and drop esteem at speed 60. Furthermore, the proposed approach brings about a Throughput of 23 contrasted with 17 for the ongoing technique. The reasonableness list of the proposed technique is 3.000000, while that of the ongoing strategy is 4.000000. The recommended approach accomplishes energy utilization, postpone worth, and drop esteem in speed 70 of 890 J, 122.32609, and 9.309993, separately. Moreover, the new method accomplishes a throughput of 9, while the old strategy just deals with a throughput of 6.

Conclusion

By routinely inspecting each network node, the given ensemble with the HFSA-VANET actually keeps up with network steadiness. Counterfeit Fish Swarm Optimization (AFSO) and Seagull Optimization are joined with the HFSA. The exhibition of the AFSO, which is utilized for VANET upgrade, is worked on by

the utilization of the seagull streamlining approach. Thus, offers unquestionably effective outputs that are inspected utilizing an outfit learning approach that incorporates ANN, SVM, DT, and Naive Bayes. The NS2 and MATLAB stages are utilized for the execution. For contrasting the presentation of the recommended calculation, the HFSA-VANET is carried out in NS2 without troupe learning and in MATLAB with gathering learning. In contrast with the CRSM-VANET approach at 80 hubs, the HFSA-VANET technique displays a general decrease in dormancy of 34%, a decrease in energy use of 81%, and an improvement in throughput of 9%. As a result, it can be demonstrated that the suggested model is an approach that is far more effective than those already in use.

Future Scope

The participating users and the aggregated data have been protected using a variety of privacy methods. More specifically, the strategies mentioned above were designed to safeguard data exchange as well as location privacy and participant identity privacy. The majority of publications tend to emphasise the employment of pseudonyms for communication, shrouding/grouping regions for area security, and homomorphic encryption to safeguard information protection to accomplish character security.



To maintain privacy, other, more sophisticated techniques are also employed in certain articles, including zero knowledge proofs ring signatures blind signatures, and group signatures. Here, it's important to draw attention to various novel privacy-preserving strategies that have been suggested, like federating learning. Albeit just four of these proposed strategies are in the evidence of idea stage not a single one of them have been tried in genuine circumstances and their security safeguarding perspective is still in principle or reproduction.

Given the previous, IoV innovations can work on restricted equipment and should consume minimal measure of energy, while the proposed agreement conventions' energy proficiency and execution should be widely and for an enormous scope confirmed. Furthermore, while blockchain is an innovation that may without a doubt make preparations for information altering, security insurance can't be ensured. As large numbers of the proposed plans address no equipment or programming needs, it is similarly essential to consider how this multitude of advancements may be associated with a current foundation and gauge the expense of incorporation. The necessities and imperatives of the Privacy-Enhancing Technologies (PETs) should be streamlined considering these highlights.

References

1. M. M. Kamruzzaman, "New Opportunities, Challenges, and Applications of Edge-AI for Connected Healthcare in Smart Cities," 2021 IEEE Globecom Workshops (GC Wkshps), 2021, pp. 1-6, doi: 10.1109/GCWkshps52748.2021.9682055."
2. MdSelimHossain, MM Kamruzzaman, ShuvoSen, Mir Mohammad Azad, Mohammad Sarwar Hossain Mollah, Hexahedron core with sensor based photonic crystal fiber: An approach of design and performance

- analysis," Sensing and Bio-Sensing Research, 32, 100426
3. Mingju Chen, Xiaofeng Han, Hua Zhang, Guojun Lin, M.M. Kamruzzaman, Quality-guided key frames selection from video stream based on object detection, Journal of Visual Communication and Image Representation, Volume 65, 2019, 102678, ISSN 1047-3203
4. M. M. Kamruzzaman: Performance of Decode and Forward MIMO Relaying using STBC for Wireless Uplink. JNW 9(12): 3200-3206 (2014)
5. M. M. Kamruzzaman, "Performance of Turbo Coded Vertical Bell Laboratories Layered Space Time Multiple Input Multiple Output system," Computer and Information Technology (ICCIT), 2013 16th International Conference on, Khulna, 2014, pp. 455-459.
6. Yan Zhang, M. M. Kamruzzaman, and Lu Feng "Complex System of Vertical Baduanjin Lifting Motion Sensing Recognition under the Background of Big Data," Complexity, vol. 2021, Article ID 6690606, 10 pages, 2021. <https://doi.org/10.1155/2021/6690606>
7. MdHossain , MM Kamruzzaman , ShuvoSen, Mir Mohammad Azad, Mohammad Sarwar Hossain Mollah , Hexahedron Core with Sensor Based Photonic Crystal Fiber, 2021
8. MdNazirul Islam Sarker, MdLamiurRaihan, Yang Peng, TahminaChumky, MM Kamruzzaman, Roger C Shouse, Huh Chang Deog, "COVID-19: Access to Information, Health Service, Daily Life Facility and Risk Perception of Foreigners during Coronavirus pandemic in South Korea," Archives of Medical Science, 2021, <https://doi.org/10.5114/aoms/141164>
9. Y. Shi, S. Wang, S. Zhou and M. M. Kamruzzaman. (2020). Study on Modeling Method of Forest Tree Image Recognition Based on CCD and Theodolite. IEEE Access, vol. 8, pp. 159067-159076, 2020, doi: 10.1109/ACCESS.2020.3018180



10. Guobin Chen, Zhiyong Jiang, M.M. Kamruzzaman. (2020). Radar remote sensing image retrieval algorithm based on improved Sobel operator, *Journal of Visual Communication and Image Representation*, Volume 71, 2020, 102720, ISSN 1047-3203 <https://doi.org/10.1016/j.jvcir.2019.102720>.
11. YuanjinXu, Ming Wei, M.M. Kamruzzaman, Inter/intra-category discriminative features for aerial image classification: A quality-aware selection model, *Future Generation Computer Systems*, Volume 119, 2021, Pages 77-83, ISSN 0167-739X, <https://doi.org/10.1016/j.future.2020.11015>.
12. Xing Li, JunpeiZhong, M.M. Kamruzzaman, "Complicated robot activity recognition by quality-aware deep reinforcement learning", *Future Generation Computer Systems*, Volume 117, 2021, Pages 480-485.
13. Bin Yuan, M. M. Kamruzzaman, Shaonan Shan, "Application of Motion Sensor Based on Neural Network in Basketball Technology and Physical Fitness Evaluation System", *Wireless Communications and Mobile Computing*, vol. 2021, Article ID 5562954, 11 pages, 2021. <https://doi.org/10.1155/2021/5562954>
14. Chi, Z., Jiang, Z., Kamruzzaman, M.M. et al. Adaptive momentum-based optimization to train deep neural network for simulating the static stability of the composite structure. *Engineering with Computers* (2021). <https://doi.org/10.1007/s00366-021-01335-5>
15. Rathore, M. S., Poongodi, M., Saurabh, P., Lilhore, U. K., Bourouis, S., Alhakami, W., ... & Hamdi, M. (2022). A novel trust-based security and privacy model for Internet of Vehicles using encryption and steganography. *Computers and Electrical Engineering*, 102, 108205.
16. Poongodi, M., Bourouis, S., Ahmed, A. N., Vijayaragavan, M., Venkatesan, K. G. S., Alhakami, W., & Hamdi, M. (2022). A Novel Secured Multi-Access Edge Computing based VANET with Neuro fuzzy systems based Blockchain Framework. *Computer Communications*.
17. Ramesh, T. R., Lilhore, U. K., Poongodi, M., Simaiya, S., Kaur, A., & Hamdi, M. (2022). PREDICTIVE ANALYSIS OF HEART DISEASES WITH MACHINE LEARNING APPROACHES. *Malaysian Journal of Computer Science*, 132-148.
18. Poongodi, M., Malviya, M., Hamdi, M., Vijayakumar, V., Mohammed, M. A., Rauf, H. T., & Al-Dhlan, K. A. (2022). 5G based Blockchain network for authentic and ethical keyword search engine. *IET Commun.*, 16(5), 442-448.
19. Poongodi, M., Malviya, M., Kumar, C., Hamdi, M., Vijayakumar, V., Nebhen, J., & Alyamani, H. (2022). New York City taxi trip duration prediction using MLP and XGBoost. *International Journal of System Assurance Engineering and Management*, 13(1), 16-27.
20. Poongodi, M., Hamdi, M., & Wang, H. (2022). Image and audio caps: automated captioning of background sounds and images using deep learning. *Multimedia Systems*, 1-9.
21. Poongodi, M., Hamdi, M., Gao, J., & Rauf, H. T. (2021, December). A Novel Security Mechanism of 6G for IMD using Authentication and Key Agreement Scheme. In *2021 IEEE Globecom Workshops (GC Wkshps)* (pp. 1-6). IEEE.
22. Ramesh, T. R., Vijayaragavan, M., Poongodi, M., Hamdi, M., Wang, H., & Bourouis, S. (2022). Peer-to-peer trust management in intelligent transportation



system: An Aumann's agreement theorem based approach. ICT Express.

23. Hamdi, M., Bourouis, S., Rastislav, K., & Mohamed, F. (2022). Evaluation of Neuro Image for the Diagnosis of Alzheimer's Disease Using Deep Learning Neural Network. *Frontiers in Public Health*, 35.

24. Poongodi, M., Hamdi, M., Malviya, M., Sharma, A., Dhiman, G., & Vimal, S. (2022). Diagnosis and combating COVID-19 using wearable Oura smart ring with deep learning methods. *Personal and ubiquitous computing*, 26(1), 25-35.

25. Sahoo, S. K., Mudligiriyappa, N., Algethami, A. A., Manoharan, P., Hamdi, M., & Raahemifar, K. (2022). Intelligent Trust-Based Utility and Reusability Model: Enhanced Security Using Unmanned Aerial Vehicles on Sensor Nodes. *Applied Sciences*, 12(3), 1317.

26. Muniyappan, A., Sundarappan, B., Manoharan, P., Hamdi, M., Raahemifar, K., Bourouis, S., & Varadarajan, V. (2022). Stability and numerical solutions of second wave mathematical modeling on covid-19 and omicron outbreak strategy of pandemic: Analytical and error analysis of approximate series solutions by using hpm. *Mathematics*, 10(3), 343.

27. Rawal, B. S., Manogaran, G., & Poongodi, M. (2022). Implementing and Leveraging Blockchain Programming.

28. Bourouis, S., Band, S. S., Mosavi, A., Agrawal, S., & Hamdi, M. (2022). Meta-Heuristic Algorithm-Tuned Neural Network for Breast Cancer Diagnosis Using Ultrasound Images. *Frontiers in Oncology*, 12, 834028.

29. Lilhore, U. K., Poongodi, M., Kaur, A., Simaiya, S., Algarni, A. D., Elmannai, H., ... & Hamdi, M. (2022). Hybrid Model for Detection

of Cervical Cancer Using Causal Analysis and Machine Learning Techniques. *Computational and Mathematical Methods in Medicine*, 2022.

30. Dhiman, P., Kukreja, V., Manoharan, P., Kaur, A., Kamruzzaman, M. M., Dhaou, I. B., & Iwendi, C. (2022). A Novel Deep Learning Model for Detection of Severity Level of the Disease in Citrus Fruits. *Electronics*, 11(3), 495.

31. Dhanaraj, R. K., Ramakrishnan, V., Poongodi, M., Krishnasamy, L., Hamdi, M., Kotecha, K., & Vijayakumar, V. (2021). Random Forest Bagging and X-Means Clustered Antipattern Detection from SQL Query Log for Accessing Secure Mobile Data. *Wireless Communications and Mobile Computing*, 2021.

32. Maurya, S., Joseph, S., Asokan, A., Algethami, A. A., Hamdi, M., & Rauf, H. T. (2021). Federated transfer learning for authentication and privacy preservation using novel supportive twin delayed DDPG (S-TD3) algorithm for IIoT. *Sensors*, 21(23), 7793.

33. Poongodi, M., Nguyen, T. N., Hamdi, M., & Cengiz, K. (2021). Global cryptocurrency trend prediction using social media. *Information Processing & Management*, 58(6), 102708.

34. Poongodi, M., Sharma, A., Hamdi, M., Maode, M., & Chilamkurti, N. (2021). Smart healthcare in smart cities: wireless patient monitoring system using IoT. *The Journal of Supercomputing*, 77(11), 12230-12255.

35. Rawal, B. S., Manogaran, G., & Hamdi, M. (2021). Multi-Tier Stack of Block Chain with Proxy Re-Encryption Method Scheme on the Internet of Things Platform. *ACM Transactions on Internet Technology (TOIT)*, 22(2), 1-20.



36. Poongodi, M., Malviya, M., Hamdi, M., Rauf, H. T., Kadry, S., &Thinnukool, O. (2021). The recent technologies to curb the second-wave of COVID-19 pandemic. IEEE Access, 9, 97906-97928.
37. Rawal, B. S., Manogaran, G., Singh, R., Poongodi, M., & Hamdi, M. (2021, June). Network augmentation by dynamically splitting the switching function in SDN. In 2021 IEEE International Conference on Communications Workshops (ICC Workshops) (pp. 1-6). IEEE.
38. Poongodi, M., Hamdi, M., Varadarajan, V., Rawal, B. S., &Maode, M. (2020, July). Building an authentic and ethical keyword search by applying decentralised (Blockchain) verification. In IEEE INFOCOM 2020-IEEE Conference on Computer Communications Workshops (INFOCOM WKSHPS) (pp. 746-753). IEEE.
39. Poongodi, M., Vijayakumar, V., Al-Turjman, F., Hamdi, M., & Ma, M. (2019). Intrusion prevention system for DDoS attack on VANET with reCAPTCHA controller using information based metrics. IEEE Access, 7, 158481-158491.
40. Poongodi, M., Hamdi, M., Sharma, A., Ma, M., & Singh, P. K. (2019). DDoS detection mechanism using trust-based evaluation system in VANET. IEEE Access, 7, 183532-183544.
41. Omarov, B., Narynov, S., Zhumanov, Z., Gumar, A., &Khassanova, M. (2022). State-of-the-art violence detection techniques in video surveillance security systems: a systematic review. PeerJ Computer Science, 8, e920.
42. Tursynova, A., & Omarov, B. (2021, November). 3D U-Net for brain stroke lesion segmentation on ISLES 2018 dataset. In 2021 16th International Conference on Electronics Computer and Computation (ICECCO) (pp. 1-4). IEEE.
43. Omarov, B., Narynov, S., Zhumanov, Z., Gumar, A., &Khassanova, M. (2022). A Skeleton-based Approach for Campus Violence Detection. CMC-COMPUTERS MATERIALS & CONTINUA, 72(1), 315-331.

